



EVERFLEX

Quality Hose Since

MANGUERA DE JEBE Y LONA



Application: Air hose(smooth surface) for versatile general industries and construction sites

NOT suitable for transfer of petroleum products

Temperature: -20°C (-4°F) to +70°C (+158°F)

Tube: Black,smooth,synthetic rubber

Reinforcement: High strength synthetic yarn

Cover: Yellow(Red/Blue/Black),smooth,synthetic rubber, weathering and ozone resistant

Optional request: ISO2398,Type1,Class A

I.D.		O.D.	Work Pressure		Burst Pressure		Max.Length	
inch	mm	mm	bar	psi	bar	psi	m	ft
3/16"	4.8	12	20	300	60	900	120	400
1/4"	6.4	13	20	300	60	900	120	400
5/16"	7.9	15	20	300	60	900	100	330
3/8"	9.5	17	20	300	60	900	100	330
1/2"	12.7	21	20	300	60	900	100	330
5/8"	15.9	26	20	300	60	900	100	330
3/4"	19.1	29	20	300	60	900	100	330
1"	25.4	36	20	300	60	900	100	330
1-1/4"	31.8	44	15	225	45	675	60	200
1-1/2"	38.1	54	15	225	45	675	60	200
2"	50.8	66	15	225	45	675	60	200



EVERFLEX

Quality Hose Since